


**I25
SERIES**



FOTON



SUNDOWN
EQUIPMENT

Hwy 92, Bevington, IA 50033
Just 15 minutes south of Des Moines at I-35 & Hwy 92

866-962-3800
www.sundownequipment.com

TRACTOR MODEL	1254	1454	1654
Drive System	4WD	4WD	4WD
Operator Area	Cab (air, heat)	Cab (air, heat)	Cab (air, heat)
PERFORMANCE			
Engine HP*	125	145	165
PTO HP*	105	122	138
Fuel Tank Capacity	84 gal	84 gal	84 gal
No. of Cylinders	6 turbo	6 turbo	6 turbo
Fuel Type	Diesel	Diesel	Diesel
Standard Shuttle Transmission	16 Fwd, 16 Rev	16 Fwd, 16 Rev	16 Fwd, 16 Rev
Speed Forward (MPH)	1.9-22.4	1.9-22.4	1.9-22.4
Clutch	Dual Stage, Dry	Dual Stage, Dry	Dual Stage, Dry
Front Tire Size	14.9-26	14.9-26	16.9-28
Rear Tire Size	18.4-38 duals	18.4-38 duals	18.4-42 duals
Brakes	Hydraulic	Hydraulic	Hydraulic
Differential Lock	Standard	Standard	Standard
PTO Type	Live	Live	Live
Speeds (RPM)	540/1,000	540/1,000	540/1,000
4WD Engagement	Mechanical	Mechanical	Mechanical
Hydraulic Outlets	3-Pioneer Ends	3-Pioneer Ends	3-Pioneer Ends
Hydraulic Output	Open System	Open System	Open System
3-Point Hitch	Position, Response	Position, Response	Position, Response
ASAE Category	Cat II	Cat II	Cat II
Stabilizers	2-Standard	2-Standard	2-Standard
3-Point Lift Capacity	7,868 lbs	7,868 lbs	7,868 lbs
Cab Doors	2	2	2
DIMENSIONS & WEIGHT			
Wheelbase	106"	106"	106"
Overall Length	17' 1"	17' 1"	17' 1"
Height to Top of Cab	10' 2"	10' 2"	10' 2"
Turn Radius	19'	19'	19'
Approx. Weight	13,670 lbs	14,450 lbs	15,430 lbs

* Foton Tractors are made by Foton Heavy Industries of China. Foton has a policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Sundown Equipment and Foton HI are not responsible for the difference between the specifications or illustrations contained in this publication.