


**30
SERIES**



FOTON



SUNDOWN
EQUIPMENT

Hwy 92, Bevington, IA 50033
Just 15 minutes south of Des Moines at I-35 & Hwy 92

866-962-3800
www.sundownequipment.com

TRACTOR MODEL	250/254	350/354
Drive System	2WD/4WD	2WD/4WD
Operator Area	Platform/Cab	Platform/Cab
PERFORMANCE		
Engine HP*	25	35
PTO HP*	22.5	31
Fuel Tank Capacity	7.7 gal	7.7 gal
No. of Cylinders	3	4
Fuel Type	Diesel	Diesel
Standard Shuttle Transmission	8 Fwd, 8 Rev	8 Fwd, 8 Rev
Speed Forward (MPH)	1.06-16.17	1.3-18
Clutch	Dual Stage, Dry	Dual Stage, Dry
Front Tire Size	6-14	5.5-16/7.5-16
Rear Tire Size	9.5-24	11.2-28
Brakes	Shoe	Double Wet Disc
Differential Lock	Standard	Standard
PTO Type	Live	Live
Speeds (RPM)	540/1,000	540/1,000
4WD Engagement	Mechanical	Mechanical
Hydraulic Outlets	Optional	2-Pioneer Ends
3-Point Hitch	Position, Response	Position, Response
ASAE Category	Cat I	Cat I
Stabilizers	Standard	Standard
3-Point Lift Capacity	1, 014 lbs	1,655 lbs
ROPS	2 Post, Foldable	2 Post, Foldable
Cab Doors	N/A	2
DIMENSIONS & WEIGHT		
	2WD/4WD	2WD/4WD
Wheelbase	65"	71"
Width	57"	61"
Overall Length	140"	140"
Height to Top of Muffler	97"	105"
Turn Radius	102"	102"
Approx. Weight	3,175 lbs/3,540 lbs	3,472 lbs/3,858 lbs

* Foton Tractors are made by Foton Heavy Industries of China. Foton has a policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Sundown Equipment and Foton HI are not responsible for the difference between the specifications or illustrations contained in this publication.