


**40
SERIES**



FOTON



SUNDOWN
EQUIPMENT

Hwy 92, Bevington, IA 50033
Just 15 minutes south of Des Moines at I-35 & Hwy 92

866-962-3800
www.sundownequipment.com

TRACTOR MODEL	400/404	500/504
Drive System	2WD/4WD	2WD/4WD
Operator Area	Platform/Cab	Platform/Cab
PERFORMANCE		
Engine HP*	40	50
PTO HP*	36	45
Fuel Tank Capacity	10 gal	10 gal
No. of Cylinders	4	4
Fuel Type	Diesel	Diesel
Standard Shuttle Transmission	8 Fwd, 8 Rev	8 Fwd, 8 Rev
Speed Forward (MPH)	1.65-21.6	2.1-21.6
Clutch	Dual Stage, Dry	Dual Stage, Dry
Front Tire Size	8.3-20	8.3-20
Rear Tire Size	12.4-24	14.9-24
Brakes	Double Wet Disc	Double Wet Disc
Differential Lock	Standard	Standard
PTO Type	Live	Live
Speeds (RPM)	540/1,000	540/1,000
4WD Engagement	Mechanical	Mechanical
Hydraulic Outlets	2-Pioneer Ends	2-Pioneer Ends
3-Point Hitch	Position, Response	Position, Response
ASAE Category	Cat I	Cat II
Stabilizers	Standard	2-Standard
3-Point Lift Capacity	1,500 lbs	1,500 lbs
ROPS	2 Post, Foldable	2 Post, Foldable
Cab Doors	2	2
DIMENSIONS & WEIGHT		
	2WD/4WD	2WD/4WD
Wheelbase	78"	78"
Width	69"	69"
Overall Length	141"	141"
Height to Top of Muffler	84"	84"
Turn Radius	134"	134"
Approx. Weight Platform	4,120 lbs/4,600 lbs	4,120 lbs/4,600 lbs
Approx. Weight Cab	5,270 lbs/5,960 lbs	4,895 lbs/5,300 lbs

* Foton Tractors are made by Foton Heavy Industries of China. Foton has a policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Sundown Equipment and Foton HI are not responsible for the difference between the specifications or illustrations contained in this publication.