


**60
SERIES**



FOTON



SUNDOWN
EQUIPMENT

Hwy 92, Bevington, IA 50033
Just 15 minutes south of Des Moines at I-35 & Hwy 92

866-962-3800
www.sundownequipment.com

TRACTOR MODEL	600/604	700/704
Drive System	2WD/4WD	2WD/4WD
Operator Area	Platform/Cab	Platform/Cab

PERFORMANCE

Engine HP*	62	70
PTO HP*	54	63
Fuel Tank Capacity	22 gal	32 gal
No. of Cylinders	4	4
Fuel Type	Diesel	Diesel
Standard Transmission	8 Fwd, 4 Rev	N/A
Shuttle Transmission	N/A	10 Fwd, 10 Rev
Speed Forward (MPH)	.50-20	.50-20
Clutch	Dual Stage, Dry	Dual Stage, Dry
Front Tire Size	6-16/8.3-20	8.3-20
Rear Tire Size	16.9-28	16.9-28
Brakes	Double Wet Disc	Double Wet Disc
Differential Lock	Standard	Standard
PTO Type	Live	Live
Speeds (RPM)	540/1,000	540/1,000
4WD Engagement	Mechanical	Mechanical
Hydraulic Outlets	2-Pioneer Ends	2-Pioneer Ends
3-Point Hitch	Position, Response	Position, Response
ASAE Category	Cat II	Cat II
Stabilizers	2-Standard	2-Standard
3-Point Lift Capacity	3,375 lbs	3,375 lbs
ROPS	2 Post, Foldable	2 Post, Foldable
Cab Doors	2	2

DIMENSIONS & WEIGHT	2WD/4WD	2WD/4WD
Wheelbase	88"	88"
Overall Length	165"	165"
Width	75"	75"
Height to Top of Muffler	103"	103"
Turn Radius w/Break	169"	169"
Approx. Weight Platform	4,825 lbs/5,225 lbs	6,632 lbs/7,032 lbs
Approx. Weight Cab	5,225 lbs/5,625 lbs	7,207 lbs/7,607 lbs

* Foton Tractors are made by Foton Heavy Industries of China. Foton has a policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Sundown Equipment and Foton HI are not responsible for the difference between the specifications or illustrations contained in this publication.