


**80
SERIES**



FOTON



SUNDOWN
EQUIPMENT

Hwy 92, Bevington, IA 50033
Just 15 minutes south of Des Moines at I-35 & Hwy 92

866-962-3800
www.sundownequipment.com

TRACTOR MODEL	820/824	900/904
Drive System	4WD	4WD
Operator Area	Cab (air, heat)	Cab (air, heat)

PERFORMANCE

Engine HP*	82	89
PTO HP*	73.8	80
Fuel Tank Capacity	40 gal	40 gal
No. of Cylinders	4 turbo	4 turbo
Fuel Type	Diesel	Diesel
Standard Shuttle Transmission	16 Fwd, 8 Rev	16 Fwd, 8 Rev
Speed Forward (MPH)	1.2-20.5	1.2-20.5
Clutch	Dual Stage, Dry	Dual Stage, Dry
Front Tire Size	11.2-24	11.2-24
Rear Tire Size	16.9-34	16.9-34
Brakes	Hydraulic	Hydraulic
Differential Lock	Standard	Standard
PTO Type	Live	Live
Speeds (RPM)	1,000	1,000
4WD Engagement	Mechanical	Mechanical
Hydraulic Outlets	2-Pioneer Ends	2-Pioneer Ends
Hydraulic Output	Open System	Open System
3-Point Hitch	Position, Response	Position, Response
ASAE Category	Cat II	Cat II
Stabilizers	2-Standard	2-Standard
3-Point Lift Capacity	3,595 lbs	3,595 lbs
ROPS	2 Post, Foldable	2 Post, Foldable
Cab Doors	2	2

DIMENSIONS & WEIGHT

Wheelbase	86.5"	86.5"
Overall Length	173"	173"
Width	80"	80"
Height to Top of Cab	110"	110"
Turn Radius	165"	165"
Approx. Weight	8,795 lbs	8,795 lbs

* Foton Tractors are made by Foton Heavy Industries of China. Foton has a policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Sundown Equipment and Foton HI are not responsible for the difference between the specifications or illustrations contained in this publication.